A55 Surface mounted light

LMA0743-0WW0A

Dimensioned drawing



Technical details

Operating voltage	22-28 VDC
Power	7 W
Connection	M12 plug
Protection	IP68
Protection class	III
Risk group	0
Length (L)	165 mm
Material	tempered float glass, anodized aluminum
Beam angle	120° diffuse
Light color	5000 K white
UL	Yes
IO-Link	No

Based on complex manufacturing process of LEDs typical values of technical LED-parameters as stated above are only statistical values, which do not comply necessarily with real technical parameters of each single product. Measurement of the light color white according to EN 62471:2008 at standard distance (illuminance = 500 lx). The risk group may vary depending on light color and application. Detailed information and measurement results are available on request.

Safety note

LED Lighting Systems are able to generate very intense radiation, which can damage eyes by inappropriate use. The LED lights may only be used in accordance with the technical data and safety regulations. The safety and installation notes refer to the whole life cycle of the LED light. In-house regulations and relevant regulations valid for the country of use must be observed. If basically safety and warning requirements are ignored, there is a danger of personal injuries and property damages. We are not liable for any damage resulting from these cases.

• Use the light in perfect technical condition. Perform a professional assembly and electrical connection. • Installation of the LED light only by qualified staff. • The light is designed for a voltage of 24 VDC and should never be operated at other voltage. • Before working on the light, disconnect the power supply. • The light cannot be opened. Unauthorized modifications of the light are prohibited. • The light is fixed with the corresponding fixing elements (available as accessories).

The suitability of the product for the intended purpose of use has to be checked by the customer.

Downloads

Download STEP-File:
https://api.diana-leuchten.de/uploads/M_LMA_0743_0x_W0x_96ec8034dd.STEP

Download 3D-PDF:
https://api.diana-leuchten.de/uploads/M_LMA_0743_0x_W0x_b9209f0d1e.PDF

Care instructions

Before cleaning the light, it must be disconnected from the power supply. If the light is dirty, it can be cleaned with a damp cloth and rubbing alcohol. Restart the light only, when there is no moisture on it. If the LED light fails, it must be checked by the manufacturer and repaired if necessary.

Mounting

The light can be mounted via four M5 flat countersinks or M6 threaded holes.

Disposal information

This product is covered by WEEE Directive 2012/19/EU on waste electrical and electronic equipment. Dispose of the product properly and not as part of the domestic waste. The regulations of the respective country are to be observed. Information is provided by the national authorities.

A55 Surface mounted light

LMA0743-0WW0A

Electrical connection



input (M12 plug, 4-pin)

PIN 1	brown	+24V
PIN 2	white	nc
PIN 3	blue	GND
PIN 4	black	nc

Light supply voltage is 24 VDC.

c UL us LISTED
LOW VOLTAGE LUMINAIRE
E503650

Isolux diagrams

Isolux diagrams 50 cm

$E_{v,max}$ = 1054.7 lx / $E_{v,m}$ = 337.5 lx



Isolux diagrams 100 cm

$E_{v,max}$ = 274 lx / $E_{v,m}$ = 179.6 lx



Isolux diagrams 150 cm

$E_{v,max}$ = 123.1 lx / $E_{v,m}$ = 100.4 lx



Isolux diagrams 200 cm

$E_{v,max}$ = 70.3 lx / $E_{v,m}$ = 62.8 lx



Measurement #100241595 from 2021-02-05
Ev,max = maximum illuminance / Ev,m = average illuminance (mean value of all illuminances over the measured measuring range) Due to the complex manufacturing process of light-emitting diodes and low measurement uncertainties, the ISO-Lux diagrams are only approximations, which do not necessarily correspond to the actual ISO-Lux diagrams of each individual product.